DC260-12

DEEP CYCLE

260AH @ 20Hr
12-Volt

Group Size: 8D

Maintenance-Free
Sealed AGM Battery



CYCLING CAPACITY

20 Hour Rate	**260 Amp Hours**

RESERVE CAPACITY

Reserve @25 AMPS	**578 Minutes**	Reserve @75 AMPS	**145 Minutes**

ELECTRICAL SPECIFICATIONS

Nominal Voltage	**12 Volt**
C100	**286AH**
C20	**260AH**
C10	**234AH**
C5	**214AH**
CCA	**1525**
CA or MCA	**1830**
HPCA	**2600 Amps**
Internal Resistance	**1.8m Ω**

MECHANICAL SPECIFICATIONS

Group Size	**8D**	
Terminal Type	**L Terminal**	
Terminal Torque	**See reverse side**	
Height (w/ terminal)	**9.65"**	**245mm**
Height (case only)	**8.66"**	**220mm**
Width	**10.59"**	**269mm**
Length	**20.51"**	**521mm**
Weight	**172.4 lbs**	**78.2 kg**
Case Type	**ABS Plastic -** Flame Res. Rating UL94-HB	

DISCHARGE TABLE (Constant Current)

Time	Amps	Rate
20hr	13.0	0.05CA
10hr	23.4	0.10CA
8hr	28.3	0.13CA
5hr	42.3	0.25CA
3hr	58.9	0.33CA
2hr	78.3	0.50CA
1hr	148	1.00CA

DISCHARGE PROFILE (Constant Current)

12-Volt Battery *Temperature: 77°F (25°C)*



- All listed ratings are @ 100% SoC, T=77°F (25°C), 1.75VPC unless otherwise specified.
- Specifications listed are for estimation purposes only. Battery performance can vary depending on application. Battery design subject to change.

BATTERY & TERMINAL DIMENSIONS (All units shown in mm)



Battery bank spacing required, 12.5mm (1/2" inch) minimum

Terminal: LT



(unit: mm)

DC260-12 DATA SHEET fullriverbattery.com

TEMPERATURE vs CAPACITY



STATE of CHARGE (SOC) vs OPEN CIRCUIT VOLTAGE (OCV)



CYCLE LIFE vs DEPTH of DISCHARGE (DOD)

*(Based on BCI Testing @ 2-hr Rate)



SELF DISCHARGE vs TIME/TEMPERATURE



Note: "Boost Charge" required @ 75% SoC, Max 50% Soc

TEMPERATURE RANGE SPECIFICATIONS

Condition	Recommended	Maximum	Recommended	Maximum
Storage	5°F to 122°F	-40°F to 160°F	-15°C to 50°C	-40°C to 71°C
Operation	5°F to 104°F	-40°F to 160°F	-15°C to 40°C	-40°C to 71°C
Charge with TC	5°F to 122°F	-40°F to 160°F	-15°C to 50°C	-40°C to 71°C
Charge w/o TC	32°F to 104°F	5°F to 122°F	0°C to 40°C	-15°C to 50°C

TC*= *Temperature Compensation

CHARGE VOLTAGES

	Battery Voltages			
Charge Stage	**12V**	**24V**	**36V**	**48V**
Bulk	14.7V	29.4V	44.1V	58.8V
Absorption	14.7V	29.4V	44.1V	58.8V
Float	13.6V	27.2V	40.8V	54.6V

TC Factor: (-2mV°F/cell) or (-4mV°C/cell)

TERMINAL TORQUE SPECS

Terminal Type	ft-lbs	in-lbs	Nm
AP, DT *(AP)*, **M6, M6M** *(Stud)*, **TP07** *(AP)* ,**TP08** *(AP)*	**4.2 - 6.0**	**50-70**	**5.6 - 7.9**
FR45	**6.0 - 7.5**	**70-90**	**7.9 - 10.1**
M8	**7.1 - 8.0**	**85-95**	**9.6 - 10.7**
DT *(Stud)*, **M10M** *(Stud)*	**9.2 - 10.4**	**110-125**	**12.2 - 14**

ISO CERTIFIED

9001:2008 Quality Management System
14001:2004 Environmental Management System
18001:2007 Occupational Health & Safety Management System

DEEP 100% CYCLE

DELIVERY APPROVED!
LAND, SEA & AIR

Fullriver batteries are sealed lead acid batteries made with Absorbed Glass Mat (AGM) technology. The electrolyte is absorbed into the fiberglass separator material rather than in a free-flowing liquid form. Fullriver batteries are non-spillable electric storage batteries. They are excepted from the requirements of DOT's hazardous materials regulations, since they adhere to the requirements of code 49 CFR Section 173.159(D) - **(CLASSIFIED APPROVED: DOT, CFR, HMR49, IATA, ICAO67, IMDG27)**